

Instructions

1. Set up anchor point (A), in firm ground at the edge of the water using a ground stake, large rock, log, tree root or anything that will hold the force of the fishing rod pulling against it (see fig 1).
2. Set up fishing rod holder (B) so that it will hold the fishing rod straight up, approximately one to one and a half rod lengths away from anchor point (A) (see fig 1).
3. Tie quickset to anchor point (A) and adjust string length to about three quarters of the distance to the fishing rod holder (adjustment will vary depending on your rod length and weight).
4. Cast line into water and set the fishing rod in the rod holder with the fishing rod eyelets facing away from the water.
5. Set quickset in the locked position. First swing the rod tip catch lever (1) up into the body second, pull the strike arm (2) back (see fig 2).
6. While holding the quickset in the locked position, bend the fishing rod tip down to the quickset and hook the rod tip catch on to the tip of the rod (see fig 3) caution do not over bend the fishing rod, it could break.
7. Tighten up slack line with the fishing reel.
8. At the rod tip pull back on the fishing line three to six inches to take the pulling pressure off the fishing line. Then loosely place the line over the peg on the strike arm. Line should be as tight as possible without pulling hard enough to release the quickset.

Caution: keep away from behind the fishing rod when in the set position, it could release at any time causing injury.

KESCO PRODUCTS
St, Louis, Missouri

